EU DECLARATION OF PERFORMANCE

	NO. 91003601-CPR-20260310	
1.	**Unique identification code of the product type**	**Scan 1003 CS**
2.	**Intended use(s)**	Solid fuel burning appliances
3.	**Manufacturer / trade mark**	Jøtul AS Postboks 1411 1602 Fredrikstad, Norway
4.	**Authorised representative**	-
5.	**System(s) of assessment and verification of constancy of performance of the construction product**	System 3
6.	**The notified test laboratory has performed the initial test according to system 3** **Notified body**	NB No 1235 (DTI) CPR-1235-ELAB-2718-REV.2
7.	**Harmonised technical specifications**	EN 16510-1:2022, EN 16510-2-2:2022
8.	**Essential characteristics**	
	Safety in case of fire*	
	Minimum distance to combustible materials - below the bottom (not regarding feet)	d_B = 0 mm
	Minimum distance to combustible materials - front to the bottom front radiation area	d_F = 0 mm
	Minimum distance to combustible materials - ceiling	d_C = 1010 mm
	Minimum distance to combustible materials - rear	d_R = 225 mm
	Minimum distance to combustible materials - side	d_S = 500 mm
	Minimum distance to combustible materials - front to the side front radiation area	d_L = 0 mm
	Minimum distance to adjacent combustible materials (e.g. furniture)	d_P = 1400 mm
	Material type and thickness of the protective insulation material	Calcium silicate boards, s= 50 mm
	Hygiene, health and environment	
	Emissions at nominal heat output	
	Carbon monoxide emission (CO)	781 mg/Nm³
	Nitrogen oxides emission (NOx)	95 mg/Nm³
	Emission of organic gaseous carbon (OGC)	35 mg/Nm³
	Particulate matter emissions (PM)	17 mg/Nm³
	Emissions at part load heat output	
	Carbon monoxide emission (CO)	NPD
	Nitrogen oxides emission (NOx)	NPD
	Emission of organic gaseous carbon (OGC)	NPD
	Particulate matter emissions (PM)	NPD

** The distances apply to stoves without insulated flue pipe*

EU DECLARATION OF PERFORMANCE

	Safety and accessibility in use		
	Data for installation to a chimney at nominal heat output		
	Flue gas outlet temperature		315 °C
	Minimum flue draught		12 Pa
	Flue gas mass flow		8.1 g/s
	Data for installation to a chimney at part load heat output		
	Flue gas outlet temperature		NPD
	Minimum flue draught		NPD
	Flue gas mass flow		NPD
	Data for installation to a chimney regarding fire safety on safety test heat output		
	Fire safety of installation to the chimney		T400 G
	Energy economy and heat retention		
	Appliance's thermal output and energy efficiency at nominal heat output		
	Space heat output		7.8 kW
	Water heat output (if available)		NPD
	Efficiency		79 %
	Appliance's thermal output and energy efficiency at part load heat output		
	Space heat output		NPD
	Water heat output (if available)		NPD
	Efficiency		NPD
	Space heating efficiency		
	Seasonal space heating efficiency at nominal heat output		69 %
	Energy Efficiency	Energy Efficiency Index (EEI)	105
		Energy Efficiency Class	A
	Electric power consumption at appliance's nominal heat output (if available)		NPD
	Electric power consumption at appliance's part load heat output (if available)		NPD
	Power consumption in standby mode (if available)		NPD
	Sustainable use of natural resources		
	Environmental sustainability		NPD
9.	The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.		

„NPD" (No Performance Determined), if no quality is stated

Signed on behalf of the manufacturer	
Place and date of issue	Fredrikstad, Norway 10.03.2026
SCAN	Lena Bergqvist (COO)